

# POWER RELAY

## 1 POLE - 16A Sealed Type

### FTR-K1 Series

#### ■ FEATURES

- 1 pole
  - 16A
  - 1 form A / 1 form C
  - Coil sensitive 400mW
  - High insulation in small package (between coil and contacts)
    - Insulation distance: 10mm min.
    - Dielectric strength: 5,000VAC
    - Surge strength: 10,000V
  - Conform to UL1446 Class F coil insulation system
  - Cadmium free contacts
  - Sealed type, RTIII
  - RoHS compliant
- Please see page 7 for more information



#### ■ PARTNUMBER INFORMATION

[Example]      FTR-K1   C   K   005   W   -   KW  
                       (a)    (b)   (c)   (d)   (e)        (f)

(a)	Relay type	FTR-K1: FTR-K1 Series	
(b)	Contact configuration	A	: 1 form A
		C	: 1 form C
(c)	Coil type	K	: Standard type (400mW)
(d)	Coil rated voltage	005	: 5.....48 VDC Coil rating table at page 3
(e)	Contact material	W	: AgSnO <sub>2</sub>
(f)	Special type	KW	: Sealed type, RTIII

Actual marking does not carry the type name : "FTR"

E.g.: Ordering code: FTR-K1CK005W-KW    Actual marking: K1CK005W-KW

# FTR-K1 SERIES

## ■ SPECIFICATION

16A type

Item	FTR-K1 CK ( ) W-KW		FTR-K1 AK ( ) W-KW
Contact Data	Configuration	1 form C	
	Construction	Single	
	Material	AgSnO <sub>2</sub>	
	Resistance (initial)	Max. 100mOhm at 1A, 6VDC	
	Contact rating (resistive)	16A, 250VAC	
	Max. carrying current *1	20A	
	Max. switching voltage	440VAC	
	Max. switching power	4,000VA	
	Min. switching load *2	100mA, 5VDC	
Life	Mechanical	Min. 20 x 10 <sup>6</sup> operations	
	Electrical	Rating resistive load	Min. 10 x 10 <sup>3</sup> operations    Min. 20 x 10 <sup>3</sup> operations
Coil Data	Rated power (20 °C)	400 / 430 mW	
	Operating temperature range	-40 °C to +105 °C (no frost)	
Timing Data	Operate (at nominal voltage)	Max. 15ms (without bounce, no diode)	
	Release (at nominal voltage)	Max. 5ms (without bounce, no diode)	
Insulation	Resistance (initial)	Min. 1,000MOhm at 500VDC	
	Dielectric strength	Open contacts	1,000VAC (50/60Hz) 1min
		Contacts to coil	5,000VAC (50/60Hz) 1min
	Surge strength	Coil to contacts	10,000V / 1.2 x 50μs standard wave
	Clearance	10mm	
	Creepage	10mm	
	EN61810-1, VDE0435	Voltage	250
		Pollution degree	3
		Material group	III a
Other		Category	C / 250V
	Vibration resistance	Misoperation≥1us	10 to 55Hz double amplitude 0.7mm
		Endurance	10 to 55Hz double amplitude 1.5mm
	Shock	Misoperation≥1us	100m/s <sup>2</sup> (11 ± 1ms)
		Endurance	1,000m/s <sup>2</sup> (6 ± 1ms)
	Weight	Approximately 13g	
	Sealing	RTIII	

\* 1: Need to consider the heat from PCB when max. current is more than 10A.

\* 2: Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

# FTR-K1 SERIES

## ■ COIL RATING

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance +/- 10% (Ohm)	Must Operate Voltage (VDC) *	Must Release-Voltage (VDC) *	Max. Coil Voltage (VDC)	Rated Power (mW)
005	5	62	3.5	0.5	12.2	400
006	6	90	4.2	0.6	14.7	
009	9	202	6.3	0.9	22.0	
012	12	360	8.4	1.2	29.4	
018	18	810	12.6	1.8	44.1	
022	22	1210	15.4	2.2	53.9	
024	24	1440	16.8	2.4	58.8	
028	28	1960	19.6	2.8	68.6	430
048	48	5360	33.6	4.8	117.6	







Note: All values in the table are valid for 20°C and zero contact current.

\* Specified operate values are valid for pulse wave voltage.







## ■ SAFETY STANDARDS

Type	Compliance	Contact rating
UL	508 E 63614	Flammability: UL 94-V0 (plastics)
VDE	0435; 40013848	16A, 250VAC cos $\varphi$ =1 85 °C 10.000 ops. (1 form A type)

## ■ CHARACTERISTIC DATA




# FTR-K1 SERIES




# FTR-K1 SERIES

## ■ DIMENSIONS


### • Dimensions



### • Drilling plan (BOTTOM VIEW)



### • Wiring diagram (BOTTOM VIEW)



Unit: mm

Note: In case of 1 form A, there is no "stationary" contact arm.

## RoHS Compliance and Lead Free Information

### 1. General Information

- All signal and power relays produced by Fujitsu Components are compliant with RoHS directive 2002/95/EC including amendments.
- Cadmium as used in electrical contacts is exempted from the RoHS directives on October 21st, 2005. (Amendment to Directive 2002/95/EC)
- All of our signal and power relays are lead-free. Please refer to Lead-Free Status Info for older date codes at: <http://www.fujitsu.com/us/downloads/MICRO/fcai/relays/lead-free-letter.pdf>
- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.

### 2. Recommended Lead Free Solder Profile

- Recommended solder Sn-3.0Ag-0.5Cu.

**Flow Solder condition:**

Pre-heating: maximum 120°C  
Soldering: dip within 5 sec. at  
260°C solder bath

**Solder by Soldering Iron:**

Soldering Iron  
Temperature: maximum 360°C  
Duration: maximum 3 sec.

**We highly recommend that you confirm your actual solder conditions**

### 3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

### 4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

## Fujitsu Components International Headquarter Offices

### Japan

Fujitsu Component Limited  
Gotanda-Chuo Building  
3-5, Higashigotanda 2-chome, Shinagawa-ku  
Tokyo 141, Japan  
Tel: (81-3) 5449-7010  
Fax: (81-3) 5449-2626  
Email: [promothq@ft.ed.fujitsu.com](mailto:promothq@ft.ed.fujitsu.com)  
Web: [www.fcl.fujitsu.com](http://www.fcl.fujitsu.com)

### North and South America

Fujitsu Components America, Inc.  
250 E. Caribbean Drive  
Sunnyvale, CA 94089 U.S.A.  
Tel: (1-408) 745-4900  
Fax: (1-408) 745-4970  
Email: [components@us.fujitsu.com](mailto:components@us.fujitsu.com)  
Web: <http://us.fujitsu.com/components>

### Europe

Fujitsu Components Europe B.V.  
Diamantlaan 25  
2132 WV Hoofddorp  
Netherlands  
Tel: (31-23) 5560910  
Fax: (31-23) 5560950  
Email: [info@fceu.fujitsu.com](mailto:info@fceu.fujitsu.com)  
Web: [emea.fujitsu.com/components/](http://emea.fujitsu.com/components/)

### Asia Pacific

Fujitsu Components Asia Ltd.  
102E Pasir Panjang Road  
#01-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: (65) 6375-8560  
Fax: (65) 6273-3021  
Email: [fcal@fcal.fujitsu.com](mailto:fcal@fcal.fujitsu.com)  
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2010 Fujitsu Components Europe B.V. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

The contents, data and information in this datasheet are provided by Fujitsu Component Ltd. as a service only to its user and only for general information purposes.

The use of the contents, data and information provided in this datasheet is at the users' own risk.

Fujitsu has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

Fujitsu Components Europe B.V. and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof.

Nor do Fujitsu Components Europe B.V. and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability for any representation or warrant of any kind, express or implied, including warranties of any kind for merchantability or fitness for particular use, with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. August 12 2010