

序号	型号	触点形式	触点容量	负载电流	负载电压(Max)	接触电阻(Max)	吸合时间(Max)	释放时间(Max)	介质耐压	线圈电压	封装
1	HVR12-2C05-02	2C	50W	3.2A	2500VDC	300mΩ	4.5ms	4.0ms	5000VDC	12VDC	PCB-THT
2	HVR12-2C05-03	2C	50W	3.2A	2500VDC	300mΩ	4.5ms	4.0ms	5000VDC	12VDC	PCB-THT
3	HVR24-2C05-02	2C	50W	3.2A	2500VDC	300mΩ	4.5ms	4.0ms	5000VDC	24VDC	PCB-THT
4	HVR24-2C05-03	2C	50W	3.2A	2500VDC	300mΩ	4.5ms	4.0ms	5000VDC	24VDC	PCB-THT
5	HVR12-2C10-02	2C	50W	5.0A	7500VDC	150mΩ	4.5ms	4.0ms	10000VDC	12VDC	PCB-THT
6	HVR12-2C10-03	2C	50W	5.0A	7500VDC	150mΩ	4.5ms	4.0ms	10000VDC	12VDC	PCB-THT
7	HVR24-2C10-02	2C	50W	5.0A	7500VDC	150mΩ	4.5ms	4.0ms	10000VDC	24VDC	PCB-THT
8	HVR24-2C10-03	2C	50W	5.0A	7500VDC	150mΩ	4.5ms	4.0ms	10000VDC	24VDC	PCB-THT