

序号	型号	触点形式	触点容量	负载电流	负载电压(Max)	接触电阻(Max)	吸合时间(Max)	释放时间(Max)	介质耐压	线圈电压	封装
1	HVR12-2A08-150	2A	50W	5.0A	2500VDC	150mΩ	3.5ms	2.0ms	10000VDC	12VDC	轴向线缆
2	HVR24-2A08-150	2A	50W	5.0A	2500VDC	150mΩ	3.5ms	2.0ms	10000VDC	24VDC	轴向线缆
3	HVR12-2A10-150	2A	50W	5.0A	7500VDC	150mΩ	3.5ms	2.0ms	15000VDC	12VDC	轴向线缆
4	HVR24-2A10-150	2A	50W	5.0A	7500VDC	150mΩ	3.5ms	2.0ms	15000VDC	24VDC	轴向线缆
5	HVR12-2A15-150	2A	50W	5.0A	10000VDC	150mΩ	3.5ms	2.0ms	15000VDC	12VDC	轴向线缆
6	HVR24-2A15-150	2A	50W	5.0A	10000VDC	150mΩ	3.5ms	2.0ms	15000VDC	24VDC	轴向线缆
7	HVR12-2A08-150YP	2A	50W	5.0A	2500VDC	150mΩ	3.5ms	2.0ms	10000VDC	12VDC	轴向线缆
8	HVR24-2A08-150YP	2A	50W	5.0A	2500VDC	150mΩ	3.5ms	2.0ms	10000VDC	24VDC	轴向线缆
9	HVR12-2A10-150YP	2A	50W	5.0A	7500VDC	150mΩ	3.5ms	2.0ms	15000VDC	12VDC	轴向线缆
10	HVR24-2A10-150YP	2A	50W	5.0A	7500VDC	150mΩ	3.5ms	2.0ms	15000VDC	24VDC	轴向线缆
11	HVR12-2A15-150YP	2A	50W	5.0A	10000VDC	150mΩ	3.5ms	2.0ms	15000VDC	12VDC	轴向线缆
12	HVR24-2A15-150YP	2A	50W	5.0A	10000VDC	150mΩ	3.5ms	2.0ms	15000VDC	24VDC	轴向线缆