

序号	型号	触点形式	触点容量	负载电流	负载电压(Max)	接触电阻(Max)	吸合时间(Max)	释放时间(Max)	介质耐压	线圈电压	封装
1	HRX10-1A10	1A	50W	5.0A	7500VDC	150mΩ	3.0ms	1.5ms	10000VDC	10VDC	轴向引脚
2	HRX12-1A10	1A	50W	5.0A	7500VDC	150mΩ	3.0ms	1.5ms	10000VDC	12VDC	轴向引脚
3	HRX24-1A10	1A	50W	5.0A	7500VDC	150mΩ	3.0ms	1.5ms	10000VDC	24VDC	轴向引脚
4	HRX10-1A10-YP	1A	50W	5.0A	7500VDC	150mΩ	3.0ms	1.5ms	10000VDC	10VDC	轴向引脚
5	HRX12-1A10-YP	1A	50W	5.0A	7500VDC	150mΩ	3.0ms	1.5ms	10000VDC	12VDC	轴向引脚
6	HRX24-1A10-YP	1A	50W	5.0A	7500VDC	150mΩ	3.0ms	1.5ms	10000VDC	24VDC	轴向引脚
7	HRX10-1A15	1A	50W	5.0A	10000VDC	150mΩ	3.0ms	1.5ms	15000VDC	10VDC	轴向引脚
8	HRX12-1A15	1A	50W	5.0A	10000VDC	150mΩ	3.0ms	1.5ms	15000VDC	12VDC	轴向引脚
9	HRX24-1A15	1A	50W	5.0A	10000VDC	150mΩ	3.0ms	1.5ms	15000VDC	24VDC	轴向引脚
10	HRX10-1A15-YP	1A	50W	5.0A	10000VDC	150mΩ	3.0ms	1.5ms	15000VDC	10VDC	轴向引脚
11	HRX12-1A15-YP	1A	50W	5.0A	10000VDC	150mΩ	3.0ms	1.5ms	15000VDC	12VDC	轴向引脚
12	HRX24-1A15-YP	1A	50W	5.0A	10000VDC	150mΩ	3.0ms	1.5ms	15000VDC	24VDC	轴向引脚